

LED Modular Light



- ⊙ Modular design, easy for maintenance.
- ⊙ Multiple Selectable projection angle, Flexible for layout.
- ⊙ Cree/Nichia chip inside.
- ⊙ High luminous efficiency, low power consumption, low luminous decay, energy saving and environment friendly.
- ⊙ Driven via constant current circuit, Each lamp's current is consistent with other such that no interference is caused.
- ⊙ Achieve best uniformity of illuminance and chromaticity by "first lens light distribution" technology.
- ⊙ Ingress protection rating: IP66.
- ⊙ Certification: CB/CE.

Product Specifications

Specification	80W	120W	160W
LED Power	75W	112.5W	150W
Luminous Flux	6000 lm	9000 lm	12000 lm
Input Voltage Range	AC 100V~240V		
Operating Frequency	50Hz / 60Hz		
Power Factor	>0.9		
Luminous Efficiency	80 lm/W		
Color Temperature	5000K		
Color Rendering Index	Ra>70		
Life Time	>50,000 Hrs		
Ambient Operating Temperature	- 30°C~ + 50°C		
Relative Humidity	10% ~ 90%		
Material	Aluminum alloy		
Wide Viewing Angle	15° / 30° / 60° / 30°*15° / 149°*72° / 145°*(17°+55°)		
IP Protection Class	IP 66		
Dimension	280*280*324.5 mm	280*375.5*324.5 mm	280*471*324.5 mm
Net Weight	6.5 kg	8.8kg	11.1 kg